

Indoor unit data and pair combinations

FTXB-C

Split series Wall mounted unit

With all features for optimal indoor climate and a bit more



(1)

INDOOR UNITS				FTXB20C	FTXB25C	FTXB35C	FTXB50C	FTXB60C	
Approximate capacity	Cooling	Min./Nom./Max.	kW	1,3/2,0/2,6	1,3/2,5/3,0	1,3/3,3/3,8	-/5,48/-	-/6,23/-	
	Heating	Min./Nom./Max.	kW	1,3/2,5/3,5	1,3/2,8/4,0	1,3/3,5/4,8	-/5,6/-	-/6,4/-	
Casing	Color			White					
Dimensions	Unit	H x W x D	mm	283x770x216			310x1065x224		
Weight	Unit		kg	8			14		
Sound power level	Cooling	High	dB(A)	55	55	58	55	61	
	Heating	High	dB(A)	55	55	58	55	61	
Sound pressure level	Cooling	High/Nom./Low/Silent operation	dB(A)	39/33/25/21	40/33/26/21	41/34/27/21	44/40/38/32	46/43/37/33	
	Heating	High/Nom./Low/Silent operation	dB(A)	(not available at time of print)					
Piping connections	Liquid	OD	mm	6,35					
	Gas	OD	mm	9,52			12,7		
	Drain	OD	mm	18,0 (Gravity drain)					
Power supply	Phase / Frequency / Voltage			Hz / V					Power is supplied from outdoor unit

FTXB-C + RXB-C pair combinations

Indoor unit	Outdoor unit	Cooling capacity kW	Heating capacity kW	Seasonal efficiency (according to EN14825)									Prices		
				Cooling				Heating (Average climate)					Indoor unit €	Outdoor unit €	Set price €
				Energy label	Pdesign kW	SEER	A.E.C. kWh	Energy label	Pdesign kW	SCOP	A.E.C. kWh				
FTXB25C	RXB25C	1,3/2,5/3,0	1,3/2,8/4,0	A+	2,5	6,00	146	A+	2,4	4,01	838	185,-	346,-	531,-	
FTXB35C	RXB35C	1,3/3,3/3,8	1,3/3,5/4,8	A+	3,3	6,05	191	A+	2,8	4,06	966	200,-	374,-	574,-	
FTXB50C	RXB50C	1,6/5,5/4,8	1,2/5,6/6,6	A+	5,5	5,93	323	A+	3,6	4,27	1.193	319,-	594,-	913,-	
FTXB60C	RXB60C	1,7/6,2/6,5	1,2/6,4/7,1	A+	6,2	6,09	358	A+	3,8	4,06	1.310	372,-	690,-	1.062,-	

Accessories for FTXB-C units

Material name	Description	Price €
-	Infra-red wireless remote controller standard included	standard

See page 55 for technical data of the RXB-C outdoor units.